

# Product Information

## AVENO ATF 8HP Fluid GREEN

0002-000188



### Description

AVENO ATF 8HP Fluid GREEN is designed on a basis of hydrocrack oils and PAO with special additives and inhibition, which guarantee the flawless function of the automatic gearbox. AVENO ATF 8HP Fluid is green in colour. AVENO ATF 8HP Fluid GREEN is an ATF of the latest generation for all 8-gear automatic gearboxes and some 6-gear automatic gearboxes from ZF. A high wear protection is guaranteed in all operating conditions.

### Instructions for use

AVENO ATF 8HP Fluid GREEN was developed for use in the new 8HP series gearboxes of ZF 8HP45, 8HP55, 8HP70, 8HP90, as well as for the 6-gear machines of the 6HP series - 6HP19X for AUDI Q7, 6HP19A and 6HP28AF. Observance of the manufacturers' original part numbers.

### Quality classification

#### Specification

- Aisin Warner AW-1
- JASO 1A LV

#### Recommendation

- Audi G 055 005, Audi G 055 162, Audi G 052 540
- BMW 83 22 0 142 516, BMW 83 22 2 305 397
- DSIH 6p805 (Geely, Ssangyong, Mahindra 6sp)
- Honda ATF DW-1
- Hyundai NWS-9638
- Hyundai/Kia SP-IV/SPH-IV/SP-IV RR
- MB 236.12, MB 236.14, MB 236.41
- Mitsubishi ATF-J3, Mitsubishi SP-IV
- Mitsubishi Diaqueen ATF-PA
- Nissan Matic-S, Nissan Matic-W
- Saab 93 165 147
- Toyota WS (JWS 3324)
- Volvo 6 speed MY2011-2013 (P/N 31256774 or 312566)
- Volvo 6 speed MY2011-2013 (P/N 31256774 or 31256675)
- VW G 052 540, VW G 055 005, VW G 055 162
- VW G 060 162, VW G 055 540 A2
- ZF Lifeguard Fluid 8

### Properties

- High and stable viscosity index
- Very good oxidation stability
- High thermal and oxidative stability
- Excellent cooling capacity
- Reliable protection against wear, corrosion and foaming
- Good lubrication properties, even at low temperatures in winter
- Coordinated friction properties

### Technical specifications

Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	25,5	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	5,5	mm <sup>2</sup> /s	DIN 51659-2:2017-02
Viscosity Index	164		DIN ISO 2909:2004-08
Appearance	GREEN		VISUELL
Density at 15°C	838	kg/m <sup>3</sup>	DIN EN ISO 12185:1997-11
Pour Point	-54	°C	ASTM D 7346:2015