## **Product Information**AVENO CLP 150

0002-000296



## Description

AVENO CLP 150 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, high-pressure capacity under impact loads. Due to the low pour point of AVENO CLP 150, the cold behavior of this product is excellent.

## Instructions for use

AVENO CLP 150 has very good properties as a lubricant. AVENO CLP 150 can therefore be used in largely all industrial areas under stress and impact loads.

Quality classification			
Specification			
• AGMA 9005-D94	• DIN 51517-3		
Recommendation			
Cincinnati Milacron	• US Steel 224		
Clean Panel Coker	• US Steel S-200		
Properties			
An excellent cold behavior	• A stable, high-pressure capacity under impact loads		
An excellent wear protection	• A low pour point		
Prevents foam formation	• Inhibits rust and corrosion		
• Zinc free, ash free			

Technical specifications			
Properties	Data	Unit	Testing under
Kinematic Viscosity at 40°C	152,3	mm²/s	DIN 51659-2:2017-02
Kinematic Viscosity at 100°C	14,8	mm²/s	DIN 51659-2:2017-02
Viscosity Index	96		DIN ISO 2909:2004-08
Appearance	YELLOW		VISUELL
Density at 15°C	887	kg/m³	DIN EN ISO 12185:1997-11
Pour Point	-27	°C	ASTM D 7346:2015